


EW270U

3D for business and pleasure



■ Picture Performance ■ User/environmentally friendly

Specifications

Technology	0.65" 1-Chip DMD, DDP2430/2431
Resolution	1280 x 800 (total 1,024,000 pixels)
Brightness	2600 ANSI lumens
Contrast	2000:1 (on/off)
Vertical Frequency (V-Sync)	48–120 Hz
Horizontal Frequency (H-Sync)	31–99 kHz
Band Width	up to 170 MHz
Projection Lamp	185 W
Lamp Life	4000 hours (low mode) ¹
Lens	F = 2.6–2.8, f = 21.1–23.0 mm
Focus/Zoom	Manual focus and zoom (zoom ratio: 1.1:1)
Throw Ratio	1.5–1.6:1
Picture Diagonal	1.02–7.62 m
Fan Noise	29 dB (low mode)
PC Compatibility	640 x 480 to 1280 x 800 pixels (compr. 1600 x 1200 pixels, incl. composite sync, sync on green available)
Video Compatibility	NTSC/NTSC 4.43, PAL (incl. PAL-M, N), SECAM, PAL-60, Comp. video: 480i/p (525i/p), 576i/p (625i/p), 720p (750p), 1080i/p (1125i/p, 60 Hz), 1080i/p (1125i/p, 50 Hz)

Features	3D ready, 6-segment colour wheel (R/G/B/W/Y/C), Wall Screen Function, Digital Keystone Correction (vertical), dynamic lamp power control, password lock, Closed Caption Function, Instant Shut Down, chain lock bar, Easy Lamp Access, Crestron Compatibility
Input Terminals	RGB: 2 x mini-D-sub 15-pin Audio: stereo-mini-jack (Ø 3.5 mm) Video: RCA, S-Video Digital: HDMI
Output Terminals	RGB: mini-D-sub 15-pin Audio: stereo-mini-jack (Ø 3.5 mm)
Communication Terminals	RS232C; D-sub 9-pin; LAN (RJ-45)
Remote Control	Projector fully control
Dimensions (W x H x D)	282 x 94 x 229 mm (not included protrusion)
Weight	2.4 kg
Power Consumption	approx. 315 W, less than 1 W Standby
Power Supply	AC 100–240 V, 50/60 Hz
Supplied Accessories	Cable set, remote control incl. batteries, soft bag, multilingual user manual (CD-ROM), quick start guide, safety manual
Optional Accessories	Optional lamp: VLT-EX240LP

¹Depending on the operation environment and application. This is an average value given by the manufacturer based on ideal conditions.



Mitsubishi Electric Europe B.V. • German Office • Visual Information Systems
Gothaer Strasse 8 • D-40880 Ratingen
Tel.: +49 (0) 21 02/4 86 92 50 • Fax: +49 (0) 21 02/4 86 73 20 • www.Mitsubishi-VIS.de

