


EW230U-ST

Impressive images, even in small spaces



■ Picture Performance ■ User/environmentally friendly

Specifications

Technology	0.65" 1-Chip DMD, DDP2430/2431
Resolution	1280 x 800 (total 1,024,000 pixels)
Brightness	2500 ANSI lumens
Contrast	2000:1 (on/off)
Vertical Frequency (V-Sync)	48–120 Hz
Horizontal Frequency (H-Sync)	31–99 kHz
Band Width	up to 170 MHz
Projector Lamp	185 W
Lamp Life	approx. 4000 hours (low mode) ¹
Lens	F = 2.6, f = 6.9 mm
Focus/Zoom	Manual focus (zoom ratio 1.1:1)
Throw Ratio	0.5:1
Picture Diagonal	1.27–7.62 m
Fan Noise	29 dB (low mode)
Audio Speaker	2 W mono
PC Compatibility	640 x 480 to 1280 x 800 pixels (compr. 1600 x 1200), incl. composite sync, sync on green available
Video Compatibility	NTSC/NTSC 4.43, PAL (incl. PAL-M, N), SECAM, PAL-60, Comp. Video: 480i/p (525i/p), 576i/p (625i/p), 720p (750p), 1080i/p (1125i/p 50/60Hz)

Features	3D Ready, 6-Segment Color Wheel (R/G/B/W/Y/C), Wall Screen Function, Digital Keystone Correction (vertical), Closed Caption Function, Dynamic Lamp Power Control, Password Lock, Instant Shut Down, Chain Lock Bar, Easy Lamp Access, Creston Compatibility
Input Terminals	RGB: 2 x mini-D-sub 15-pin Audio: stereo-mini-jack (Ø 3.5 mm) Video: RCA, S-VIDEO Digital: HDMI
Output Terminals	RGB: mini-D-sub 15-pin Audio: stereo-mini-jack (Ø 3.5 mm)
Communication Terminals	RS232C, D-sub 9-pin, LAN (RJ-45)
Remote Control	Projector fully control
Dimensions (W x H x D)	282 x 94 x 229 mm (not included protrusion)
Weight	2.8 kg
Power Consumption	max. 315 W, less than 1 W standby
Power Supply	AC 100–240 V, 50/60 Hz
Supplied Accessories	Cable Set, Remote Control (incl. batteries), Soft Bag, Multilingual User Manual (CD-ROM), Quick Start Guide, Safety Manual
Optional Accessories	Optional lamp (VLT-EX240LP)

¹Depending on the operation environment and application. This is an average value given by the manufacturer based on ideal conditions.



Mitsubishi Electric Europe B.V. • German Office • Visual Information Systems
Gothaer Strasse 8 • D-40880 Ratingen
Tel.: +49 (0) 21 02/4 86 92 50 • Fax: +49 (0) 21 02/4 86 73 20 • www.Mitsubishi-VIS.de

