



XD600U

Putting efficiency in a favourable light



■ Picture Performance ■ Presentation ■ User/environmentally friendly

Specifications

| | |
|-------------------------------|--|
| Technology | 0.7" 1-Chip DMD, 12° LVDS, DDP2230 |
| Resolution | 1024 x 768 (total 786,432 pixels) |
| Brightness | 4500 ANSI lumens |
| Contrast | 2000:1 (on/off) |
| Vertical Frequency (V-Sync) | 50–85 Hz |
| Horizontal Frequency (H-Sync) | 15–80 kHz |
| Band Width | up to 110 MHz |
| Projection Lamp | 230 W |
| Lamp Life | approx. 5000 hours (low mode) ¹ |
| Lens | F/2.4–2.8, f = 20.6–30.1 mm |
| Focus/Zoom | Manual focus und zoom (zoom ratio: 1.5:1) |
| Throw Ratio | 1.4–2.1:1 |
| Picture Diagonal | 1.02–7.62 m |
| Fan Noise | 29 dB (low mode) |
| Audio Speaker | 10 W Mono |
| PC Compatibility | 640 x 480 to 1024 x 768 pixels (compr. 1280 x 1024 Pixel), sync on green available |
| Video Compatibility | NTSC/NTSC 4.43, PAL (incl. PAL-M, N), SECAM, PAL-60, Comp. video: 480i/p (525i/p), 576i/p (625i/p), 720p (750p), 1.080i (1125i 60 Hz), 1080i (1125i 50 Hz) |
| Features | Password lock, Instant Shut Down, Wall Screen Function, Digital Keystone Correction (vertical), Closed Caption Function, Audio Mix Function, dynamic lamp power control, chain lock bar, RS232C, LAN control, Easy Lamp Access |

| | |
|-------------------------|--|
| Input Terminals | Audio: 2 x stereo-mini-jack (Ø 3.5 mm), 2 x mini-D-sub 15-pin (1 x PC1, 1 x PC2) Video: RCA, S-Video Digital: HDMI Video Audio: RCA (L/R) |
| Output Terminals | PC (RGB): mini-D-sub 15-pin Audio: stereo-mini-jack (Ø 3.5 mm) |
| Communication Terminals | RS232C, mini-DIN 8-pin, LAN (RJ-45) |
| Remote Control | Complete operation of the projector |
| Dimensions (W x H x D) | 345 x 129 x 270 mm |
| Weight | 3.6 kg |
| Power Consumption | approx. 390 W, less than 1 W Standby |
| Power Supply | AC 100–240 V, 50/60 Hz |
| Supplied Accessories | Cable set, remote control (incl. batteries), soft bag, multilingual user manual (CD-ROM), safety manual incl. quick start guide, lens cap, lamp replacement attachment |
| Optional Accessories | Optional lamp: VLT-XD600LP |

¹Depending on the operation environment and application. This is an average value given by the manufacturer based on ideal conditions.

Mitsubishi Electric Europe B.V. • German Office • Visual Information Systems
Gothaer Strasse 8 • D-40880 Ratingen
Tel.: +49 (0) 21 02/4 86 92 50 • Fax: +49 (0) 21 02/4 86 73 20 • www.Mitsubishi-VIS.de

